
AISIN SMF BATTERY


AISIN MODEL (on carton box and sticker)	Group No.	SPECIFICATIONS										
		AH (C20)	RC (Min)	CCA (-18°)	CCA (-25°)	DIMENSIONS (mm)				TERMINAL		HOLD DOWN
						L	W	H	TH	LAY-OUT	TYPE	
55B24L	B24	45	57	360	460	237	128	200	222	0	3	B00
55B24LS	B24	45	57	360	460	237	128	200	222	0	1	B00
55D23L	D23	60	80	460	595	229	175	201	222	0	1	B01
55D23R	D23	60	80	460	595	229	175	201	222	1	1	B01
48D26L	D26	50	58	360	450	260	172	200	221	0	1	B15
48D26R	D26	50	58	360	450	260	172	200	221	1	1	B15
80D26L	D26	70	98	500	610	260	172	200	221	0	1	B15
80D26R	D26	70	98	500	610	260	172	200	221	1	1	B15
55559	L2	55	66	410	520	242	175	190	190	0	1	B13
56638	L3	66	80	460	570	278	175	190	190	0	1	B13
57412	L3	74	98	500	605	278	175	190	190	0	1	B13
58043	L4	80	110	590	720	315	175	190	190	0	1	B13

DRAWING / LAYOUT


A) TERMINAL LAYOUT



B) TERMINAL DESIGN




01



03

C) HOLD DOWN



B01 | B13 | B15 | B09

Distributed by:

NEWEAST Beyond Genuine

New East Building
Al Maktoum Street, Deira, Dubai
T: +971 4 228 1466
E: Sales@neweast.co

AISIN ASIA MIDDLE EAST & AFRICA

Addess: 507, platinum tower, cluster I, Jumeirah Lake towers, Dubai UAE.
Email : info@aisin.ae

Website : www.aisin.ae

AISIN

SMF BATTERY



Giving Your Car The
RIGHT POWER
At The RIGHT TIME



Hold Down (Hook Feet)
Designed precisely, according to standards Japanese, European, Chinese and Korean cars

Strong and Light Casing
Exclusive casing design with maximum strength protects the battery from vibrations and impacts.

OEM — Produced with standards Genuine parts (OEM)

Unattended No hassle

HIGH CCA — Optimal engine starting in all weather


STRONG DURABILITY — Precision design and more durable

Magic Eye Indicator

Monitor battery condition easily



New Alloy Grid



By using the new alloy technology on battery grid, the corrosion interface is more uniform, and the grains are thinner.


Improves the lifespan of battery

DuraLife Separator Technology



Carbon Additives

The addition of highly conductive carbon materials can refine the crystal size of lead sulfate during high-rate discharge




The addition of highly conductive carbon materials improves the HRPSoC cycle life by more than 25%.

AISIN SMF BATTERY


AISIN MODEL (on carton box and sticker)	Group No.	SPECIFICATIONS										
		AH (C20)	RC (Min)	CCA (-18°)	CCA (-25°)	DIMENSIONS (mm)				TERMINAL		HOLD DOWN
						L	W	H	TH	LAY-OUT	TYPE	
55B24L	B24	45	57	360	460	237	128	200	222	0	3	B00
55B24LS	B24	45	57	360	460	237	128	200	222	0	1	B00
55D23L	D23	60	80	460	595	229	175	201	222	0	1	B01
55D23R	D23	60	80	460	595	229	175	201	222	1	1	B01
48D26L	D26	50	58	360	450	260	172	200	221	0	1	B15
48D26R	D26	50	58	360	450	260	172	200	221	1	1	B15
80D26L	D26	70	98	500	610	260	172	200	221	0	1	B15
80D26R	D26	70	98	500	610	260	172	200	221	1	1	B15
55559	L2	55	66	410	520	242	175	190	190	0	1	B13
56638	L3	66	80	460	570	278	175	190	190	0	1	B13
57412	L3	74	98	500	605	278	175	190	190	0	1	B13
58043	L4	80	110	590	720	315	175	190	190	0	1	B13

DRAWING / LAYOUT

A) TERMINAL LAYOUT




B) TERMINAL DESIGN



01 | 03

C) HOLD DOWN



B01 | B13 | B15 | B09

AISIN

ايسين

بطارية آيسين SMF



تعطي سيارتك
القوة الصحيحة
في الوقت المناسب



اضغط للأسفل (قدم الخطاف)
مصممة بدقة، وفقا للمعايير
السيارات اليابانية والأوروبية والصينية والكورية

غلاف قوي وخفيف
تصميم غلاف حصري بأقصى قوة
يحمي البطارية من الاهتزازات والتأثيرات.

ORIGINAL EQUIPMENT OEM MANUFACTURER
أنتجت مع المعايير قطع الغيار الأصلية (OEM)

لا تحتاج للصيانة

HIGH CCA
بدء تشغيل المحرك الأمثل في جميع الأحوال الجوية


STRONG DURABILITY
تصميم دقيق وأكثر متانة

مؤشر العين السحرية

مراقبة حالة البطارية بسهولة



شبكة سبائك جديدة



باستخدام تكنولوجيا شبكة السبائك الجديدة، واجهة التآكل منتظمة أكثر و الحبيبات أرق

ترفع العمر الافتراضي للبطارية

DuraLife Separator Technology



كربون اضافي

اضافة مواد كربونية عالية الموصلية
يحسن من الحجم البلوري لكبريتات الرصاص خلال معدلات التفريغ العالية



اضافة كربون عالي الموصلية يعمل على تحسين العمر الدوري ل HRPSoC الأكثر من 25%